

Log Service

FAQs

FAQs

Basic questions

What is the Log Service?

The Log Service is a platform service used to collect, store, and subscribe to logs. The service enables you to collect in real time, centrally manage and consume various types of logs.

What functions does the Log Service provide?

1. Multiple ways of logging (using APIs, SDKs, and Logtail)
2. Definition of log collection and parsing methods using Logtail according to your need
3. Management of log collection on thousands of machines in machine groups
4. Real-time log consumption and subscription
5. Simple configuration through the console, allowing you to perform all operations through the Web
6. Seamless interconnection between the background and Alibaba Cloud products

How do I activate the Log Service?

Currently, the Log Service is in the open public beta stage. Visit www.aliyun.com, log on to your Alibaba Cloud account, go to the Log Service product page, and click "Activate Now" .

What are the basic concepts of the Log Service?

1. Core concepts: project (basic unit of log management), LogStore, shard, topic (applicable to level-2 LogStore classification), log (number of logs), and LogGroup
2. Concepts about log collection: Logtail configuration (which defines how to collect logs) and machine group (used to manage machines in groups)

What are the components of the Log Service?

The Log Service consists of a log collection agent, a server, and other systems. Currently, the log collection agent is Logtail compatible with Windows and Linux. The server is responsible for reading, writing, and configuring Log Service APIs. Other systems include MaxCompute, to which the Log

Service synchronizes logs. The Log Service will include the ability to synchronize logs to OSS and AMR for consumption.

How is a log defined in the Log Service?

A log contains three parts: time (mandatory), log content (which consists of key– value pairs), and metadata (data source, which can be defined by the IP addresses of logs).

How does the Log Service work with other Alibaba Cloud services?

1. ECS: You can install Logtail (agent) to collect logs on your ECS server.
2. MaxCompute: Logs collected to the Log Service can be automatically posted to your MaxCompute table for online query and offline analysis.

Log management

How does the Log Service store and manage user logs?

LogStores are the basic units for storing and querying logs in the Log Service. Each LogStore stores a specific type of logs. Currently, you can add, delete, modify, and query LogStores on the Log Service Console or using APIs. After creating a LogStore, you can write logs into it through APIs or SDKs. The Log Service provides Logtail to collect logs on Alibaba Cloud ECS servers in an easy way.

Are logs lost after I delete a LogStore?

Yes. Exercise caution for LogStore deletion.

What is the log storage period of the Log Service? Can I modify this period?

The following three functions of the Log Service are related to the log storage period:

- LogHub: provides temporary storage for recent 48 hours to support real-time log consumption. Currently, the storage period cannot be modified.
- LogShipper: After logs are posted to OSS and MaxCompute, you can set a lifecycle in these products.
- LogSearch: supports storage periods of seven days, 30 days, and 90 days. The storage period is unchangeable once created. Because log indexes are hot data, select OSS or MaxCompute for a longer period of cold storage.

Can I share logs with other users?

Currently, the Log Service supports RAM, allowing you to share data through subaccount authorization.

日志采集

Log collection

What types of logs does the Log Service collect?

The Log Service supports timestamped text logs encoded in UTF-8 that are generated within the past seven days and are no more than 15 minutes later than the current time.

In what ways does the Log Service collect logs? How do I choose among them?

The Log Service supports direct data writing using APIs (SDKs are currently available in four languages: Java, Python, PHP, and C#). It provides Linux- and Windows-compatible Logtail used to collect real-time updated logs from disk files.

1. If the logs generated by application programs are not flushed into disk, those logs can be written directly to the Log Service through APIs.
2. Logs that are written into disks in real time can be collected by Logtail.

How does the Log Service collect logs from ECS?

You can use Logtail to collect the ECS logs that are flushed into disk as follows:

1. Create a LogStore on the Log Service Console.
2. Perform Logtail configuration.
3. Create a machine group.
4. Execute the installation script to install the Logtail agent.
5. Apply the Logtail configurations to the desired machine group.

Does the Log Service collect historical logs?

You can only write data generated during the past seven days using an API. However, Logtail does

not support historical data collection for the moment.

What data collection capability does the Log Service provide? Does it have any limitation?

You can adjust the number of shards in a LogStore as needed. Logtail collects data at a maximum rate of 1 MB/s on ECS.

What should I pay attention to when using Logtail to collect logs on NAS?

For collection of Nginx access logs, the Nginx configurations of web servers are the same. Logs are written into files with the same name on different machines. (In this case, Logtail collects logs properly.) When NAS is used, Logtail may have missing logs or encounter a collection error if the Nginx logs on multiple machines are written into the same file on NAS (concurrent write to the same file). To avoid this problem, ensure that the logs on different web servers are written into different files on NAS.

Logtail

What is Logtail?

Logtail is a log collection agent provided by the Log Service. Once installed on your machine, Logtail monitors specified log files and automatically uploads the new logs written into these files to your designated LogStore.

Does Logtail collect static log files?

Logtail monitors file changes based on change events in the file system and sends logs generated in real time to the Log Service. Logtail does not collect the content of unchanged logs.

What platforms does Logtail support?

Currently, Logtail supports 64-bit Linux systems.

How do I install and upgrade the Logtail agent?

Installation: Install the Logtail agent using an installation script. Upgrade: The Log Service regularly upgrades the Logtail agent without interrupting the data collection process.

How do I configure the Logtail agent?

Refer to Logtail collection configuration on the console.

How does Logtail work?

1. On the console, configure the directory you want to monitor, the name of the log file, and the related parsing rule (regular expression).
2. When a log file is changed on your machine, Logtail receives an event from the file system and reads the new log.
3. Logtail parses the log format based on the regular expression and sends the log to the Log Service.

Does Logtail support log rotation?

When the log file a.LOG reaches a given size or lasts for a given period of time since created, a.LOG is renamed a.LOG.1 (or another name). A new a.LOG file is created for writing new logs. This process is called rotation. Logtail automatically rotates logs based on event notifications from the file system.

How does Logtail handle network exceptions?

In the case of a network exception or write quota overrun, Logtail caches collected logs to the local disk and resends those logs later. The maximum disk cache capacity is 500 MB. Newly cached data overwrites the old one when the 500-MB limit is exceeded. Cached files that fail to be sent to the Log Service within 24 hours are automatically deleted.

What is the log collection delay of Logtail?

Logtail collects logs based on events and sends collected logs to the Log Service within 3s.

How does Logtail process historical logs?

Logtail only collects real-time logs. If the logging time is more than 5 minutes different from the system time at which Logtail processes the log, the log is regarded as a historical log.

How long does a change in log collection configuration take effect for the Log Service?

After you apply configurations to a machine group on the console, Logtail loads and applies the configurations in 3 minutes or less.

How do I locate any log collection problems of Logtail?

1. Check whether the Logtail heartbeat is normal. If it is abnormal, **reinstall Logtail**.
2. Check whether the log files in log collection configuration are generated in real time.
3. Check whether the regular expression in log collection configuration matches the log content. If the regular expression does not match, view the error in the Logtail run log (Linux:/usr/local/ilogtail/ilogtail.LOG).

Why is the Logtail heartbeat abnormal?

1. Currently, the Logtail agent only supports 64-bit Linux operating systems.
2. Use **LogStash** to collect logs in a Windows system.

If the Logtail heartbeat is abnormal, follow the steps below to perform diagnosis.

- Check whether the Logtail process exists by running the following command. If the process does not exist, **reinstall Logtail**. If it exists, go to the next step.

```
sudo /etc/init.d/ilogtaild status
```

Run the following commands to check network connectivity:

Classic network

```
telnet logtail.cn-<region>-intranet.log.aliyuncs.com 80
```

VPC

```
telnet logtail.cn-<region>-vpc.log.aliyuncs.com 80
```

If your machine is not connected, perform the following check:

1. If the machine is configured with host name binding (run the `hostname` command to view the host name; the related file is `/etc/hosts`), check whether the bound IP address is the same as that in the Log Service machine group.
2. If no host name is bound, check whether the IP address of the machine's first network adapter is the same as that in the Log Service machine group.

If the machine is not connected, the Log Service cannot receive heartbeat packets from the machine. In this case, contact the Log Service technical support team for troubleshooting.

If the problem persists, submit a ticket in the [ticket system](#). The Log Service technical support team will look into the problem.

Currently, the Logtail agent only supports 64-bit Linux and Windows operating systems. If the Logtail heartbeat is abnormal, follow the steps below to perform diagnosis.

Linux

Check whether the Logtail process exists. by running the following command. If it does not exist, reinstall Logtail. If it exists, go to the next step. Install logtail.

```
sudo /etc/init.d/ilogtailed status
```

If the Logtail process is normal, open the file `/usr/local/ilogtail/ilogtail.LOG`.

Find config

```
[2016-12-12 12:07:10.968201] [INFO] [3726]  
[build/release64/sls/ilogtail/AppConfig.cpp:212] config server:http://logtail.cn-hangzhou-  
intranet.log.aliyuncs.com https config server:https://logtail.cn-hangzhou-  
intranet.log.aliyuncs.com
```

Identify the region where your project is located and check whether the region matches that in config. In the example, the project is located in the Hangzhou region and accessed through the intranet. **Endpoint**.

If they match, check network connectivity.

Classic network

```
telnet logtail.cn-<region>-intranet.log.aliyuncs.com 80
```

VPC

```
telnet logtail.cn-<region>-vpc.log.aliyuncs.com 80
```

Internet

```
telnet logtail.cn-<region>.log.aliyuncs.com 80
```

If the regions match and network connectivity is normal, find the code starting with UUID.

```
[2016-12-12 12:07:10.970278] [INFO] [3726] [build/release64/sls/ilogtail/elogtail.cpp:113]  
Logtail started, appInfo:{ "UUID" : "92B9E907-6D2F-4F1E-B856-  
32A8C06F2BF6" , "hostname" : "machinename" , "instance_id" : "A1841794-B793-
```



```
11E6-B8FF-00163E2EBA3C" , "ip" : "XXX.XXX.XXX.XXX" , "logtail_version" :  
  "0.11.6" , "os" : "Linux; 2.6.32-573.22.1.el6.x86_64; #1 SMP Wed Mar 23 03:35:39 UTC  
2016; x86_64" , "update_time" : "2016-12-12 12:07:10" }
```

Find the following "IP address" : "XXX.XXX.XXX.XXX" . The IP address must be configured on the console; otherwise, no heartbeat exists.

If the IP address is null in the file, your machine does not have the first network adapter (ifconfig eth0). In this case, bind the hosts file manually.

```
vi /etc/hosts
```

Add and save the first line.

```
XXX.XXX.XXX.XXX machinename
```

XXX.XXX.XXX.XXX can be filled with the IP address of another network adapter and is used as a heartbeat tag. It must match the IP address configured on the console. Run the hostname command to set machinename.

The IP address configured on the console must match that in the file. The IP address is only a tag and does not affect network access. The method of setting this IP address is as follows: Obtain the bound IP address in /etc/hosts. If no IP address is bound, obtain the IP address of the first network adapter (ifconfig eth0). The IP address is generated in the /usr/local/ilogtail/ilogtail.LOG file. You can just check this file.

If no problem is found, check whether the /usr/local/ilogtail/ilogtail.LOG file is correct. Unauthorized ErrorMessage:no authority, denied by ACL

If a problem exists, your primary account does not have the access key, causing Logtail to run abnormally. Go to ak-console.aliyun.com to create an access key. Then Logtail resumes its heartbeat.

If Logtail still does not have any heartbeat, submit a ticket.

Windows

The troubleshooting method is similar to that in Linux. The Logtail log is recorded in the file C:\Program Files (x86)\Alibaba\Logtail\logtail_0.log.

日志查询

Log query

What methods does the Log Service provide for you to query collected logs?

The Log Service provides three log query methods:

1. Log Service Console.

1. SDKs (available in C++, Java, PHP, .Net, and Python). For details, refer to SDKs.
2. RESTful APIs. For details, refer to API.

What query capabilities does the Log Service provide?

1. Query by a combination of criteria. For details about the query syntax, refer to LogSearch syntax.
2. Query 10 million logs at a time. Based on the criteria you specify, you can query the desired logs, read the time-based distribution of matched logs or obtain the raw logs.
3. Caching of queried logs, allowing you to get better results for a second query by the same criteria.

What are the constraints of LogSearch?

1. The Log Service supports queries based on a combination of up to 10 keywords.
2. Up to 100 lines of raw data are returned for a single query.
3. Up to 10 million lines of data are processed in a single query.

What if no query results are returned?

1. Go to the "LogStore List" page, find the "Log Consumption" column in "Log Consumption Mode", click "Preview", and select "ShardID" to check whether data exists.
 - If data exists, return to the "Query" page of the "Log Index" column. Click the "Topic" text box next to the "Keyword" search box, and check for topics.
 - If topics exist, select a topic and click "Query" to check whether data exists.
 - If neither topics nor data exists after you click "Query", submit a ticket to Alibaba Cloud.
 - If no data exists, check whether the collected data is complete.

The Log Service provides two functions related to the read operation.

Log collection and consumption (LogHub): provides public channels for log collection and distribution, sequential (FIFO) read and write of full data, and functions similar to Kafka.

- Each LogStore has one or more shards. Data is written to a specific shard at random.
- You can read logs in batches from the specified shard according to the log write sequence.
- You can set the starting point (cursor) of batch log pulling from shards based on the time when the Log Service receives logs.
- By default, logs are retained in LogHub for two days, during which logs can be consumed.

LogSearch (index): The LogSearch function is provided based on LogHub and supports massive log query. Data is queried randomly based on keywords.

- Acquisition of only keyword-matched data
- Boolean combination of keywords AND, NOT, and OR
- Data is queried based on all shards.

Difference:

Function	LogSearch	Log collection and consumption (based on LogHub)
Keyword search	Supported	Not supported
Reading of small data volumes	Fast	Fast
Full data reading	Slow (100 logs every 100 ms, not recommended)	Fast (1-MB logs every 10 ms, recommended)
Reading by topic	Yes	No. Data is read by shard.
Reading by shard	No. Data is queried based on all shards.	Yes. A shard must be specified for the read operation.
Fee	Relatively high	Low
Application scenario	Data filter is performed for monitoring and troubleshooting.	Full processing scenarios such as stream computing and batch processing

日志投递

RAM